Large Format Print Solutions ideal for CAD, GIS, Poster & In-house Print.

iPF510

you can

iPF510 **17** INCH 2,400 X 1,200DPI 5 COLOURS A2 IN 21 SECONDS 15,360 NOZZLES BORDERLESS PRINTING ECONOMY PRINTING MODE



The imagePROGRAF iPF510 is a 17"/A2

large format printer which combines the

productivity and return on investment.

highest of quality with exceptional

Key features

- Sharper, thinner lines and high black density for CAD plan production
- Great colour output with brilliant text and less abrasion
- Economy mode for lower running costs reduces ink consumption
- Superb graphics with vivid colours and solid image consistency
- Incredible print speeds A2 in 20 seconds
- HPGL/2 and HP/RTL compatibility and includes HDI Driver for CAD applications

- Large, bright and easy to use LCD operation panel easy access to sophisticated functions
- Compact and quiet it's the output not the noise that gets you noticed
- Bundled with free of charge PosterArtist Lite poster creation software - makes it easy to produce professional looking posters
- Borderless printing, so no need for offline trimming saving time and money
- Choice of printer driving settings tailored to suit expertise of user
- User friendly simple roll paper loading and control the print from the front
- Print plug-in for MS Office applications



🔬 imagePROGRAF

Specifications: iPF510

Model	iPF510	MEDIA SIZE	
Class Ink Type	17-inch Dye and pigment reactive ink: BK, MBK x 2, C, M, Y	Roll paper (width)	A3, A2, JIS, B4, 8", 10", 14", 16", 17", 300 mm, A3+ (329 mm)
Maximum Print Resolution Installation	2, 400 x 1, 200 dpi User installation	Cut sheet (cassette)	A4, A3, A3+, A2, B4, B3, Letter (8.5 x 11"), Legal (8.5 x 14"), 11 x 17", 13 x 19", 17 x 22", 12 x 18", 14 x 17", 12 x 16", 10
PRINTING SPEED (A2 ROLL)			x 12", 10 x 15", 8 x 10", 16 x 20" (US Photo size), 300 x 900 mm 13 x 22"
Plain paper	0:20 (Draft)	Cut sheet (front manual feed)	A2, 17 x 22", 13 x 22"
Coated Paper Photo Glossy Paper	0:55 (Standard) 1:38 (Standard)	MEDIA THICKNESS	
PRINTER STAND		Roll	0.07 - 0.8 mm
Туре	Optional, Assembly type	Cassette	0.08 - 0.3 mm
Installation conditions	User installation	Manual feed from the top Manual feed from the front	0.07 - 0.8 mm 0.5 - 1.5 mm
DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg)		MEDIA WIDTH	
Main unit	819 (W) x 733 (D) x 317(H) mm (printer only),	Roll	203 - 432 mm
	Weight: approx. 39 kg (printer, cassette, output tray, manual feed tray)	Cassette Manual feed from the top	203 - 432 mm 203 - 432 mm
Main unit with Auto Roll	819 (W) x 810 (D) x 344 (H) mm, Weight: approx. 43 kg (printer,	Manual feed from the front	203 - 432 mm
Feed Unit (Option) Main unit with Printer Stand	cassette, output tray, manual feed tray plus Auto Roll Feed Unit) 819 (W) x 981 (D) x 989 (H) mm, Weight: approx. 58 kg	MINIMUM PRINTABLE LENGTH	
	(Auto Roll Feed Unit included, consumables excluded)	Roll Cassette	203 mm 279 mm
DIMENSIONS, WEIGHT		Manual feed from the top	279 mm
(Packaged) W x D x H (mm), (kg)	960 (M) x 87/ (D) x 678 (L) mm (Maight approx 57 kg	Manual feed from the front	520 mm
Main unit with palette Printer Stand	960 (W) x 874 (D) x 638 (H) mm ; Weight: approx. 57 kg 1115 (W) x 864 (D) x 237 (H) mm ; Weight: approx. 22 kg	MAXIMUM PRINTABLE LENGTH	
POWER		Roll	18 m (varies according to the OS and application)
Input power	AC 100 - 120 V (50/60Hz), AC 220 - 240 V (50/60Hz)	Cassette Manual feed from the top	594 mm 610 mm (1.6 m when Auto Roll Feed Unit is attached)
Power consumption Power Save Mode	Operation: 100 W or less	Manual feed from the front	914 mm
100 V - 120V 220 V - 240 V	5 W or less (10 W or less when IEEE1394 is mounted) 6 W or less (11 W or less when IEEE1394 is mounted)	BORDERLESS PRINTING (ROLL MEDIA ONLY)	
Power off (standby)	1 W or less	(ROLL MEDIA ONLY) Media type	Heavyweight Coated Paper, Premium Matte Paper, Glossy Photo
Operational Environment	Temperature: 15 - 30°C, Humidity: 10 - 80 % (Condensation free)	incuta type	Paper, Semi-Glossy Photo Paper, Extra Matt Coated Paper, Opaque
ACOUSTIC NOISE Acoustic pressure	Operation: approx. 52 dB (A) or less,		Paper, Matt Coated Paper 140g, Photo Realistic Paper 210g, Instant Dry Papers Glossy 200g, Instant Dry Papers Satin 200g, Photo
	Standby: approx. 35 dB (A) or less		Paper High Glossy 250g, Photo Paper Satin 240g, Photo Paper Semi Matt 250g, Photo Paper Pearl 260g, Hi Res Barrier Paper
Acoustic power Minimal Line Width	6.6 Bels 0.02 mm (Theoretical value)	Media width	10" (254 mm), B4 (257 mm), A3+ (329 mm), 14" (356 mm),
Line Accuracy	±0.1 % or less		16" (407 mm), A2 (420 mm), A2+/17" (432 mm)
MEMORY		MEDIA FEED CAPACITY	
Standard memory	192 Mbyte	Cassette	For plain paper of 75g/m2, A4/Letter size: 25 mm (250 sheets), - A3+: 100 sheets, - A2: 50 sheets
PRINTER LANGUAGES		Manual feed	1 sheet
Printer language	GARO (Graphic Arts language with Raster Operations), HP-GL/2, HP RTL	REGULATIONS	Electrical safety regulations, Electromagnetic interface regulations
OPERATION PANEL		Europe	CE mark (EN60950, EN55022 classB, EN61000-3-2, EN-61000-3-3, EN55024)
Display	LCD	Germany Russia	TUV, GS (not declared on the plate) Gost-R (locally obtained)
Languages	US-English, French, German, Italian, Spanish	Other countries	CB certification
INTERFACE	Duilt in	ENVIRONMENT CERTIFICATIONS	
USB2.0 Hi-Speed Ethernet	Built-in Built-in		ENERGY STAR (WW), RoHS directive, IT ECO Declaration
Standard Protocol	10base-T, 100base-TX IPX/SPX, SNMP HTTP, TCP/IP, AppleTalk		(Europe), WEEE,
Optional	IEEE1394 Slot Card Type	OPTION	
Expansion Slot PRINT HEAD	1	IEEE1394 Expansion Board Auto Roll Feed Unit	EB-05 RU-02 (including 2-inch core roll holder with 3-inch paper tube
Model	PF-03	Printer Stand	attachment and borderless print spacer) ST-11
Туре	Bubble-jet on demand	Basket	BU-02
Head configuration Nozzle pitch	6 colours integrated type (1 print head) 1, 200 dpi x 2	Roll Holder Set	RH2-11 (2-inch core roll holder with 3-inch paper tube attachment and borderless print spacer)
Droplet size Head replacement	4 pl (per colour) User replacement	CONSUMABLES	
INK TANK		Ink Tank	PFI-102 (MBK, BK, C, M, Y)
Model	PFI-102 (MBK, BK, C, M, Y)	Print Head Maintenance Cartridge	PF-03 MC-05
Colours Capacity	MBK x 2, BK, C, M, Y Bundled starter ink : 90 ml, sales ink : 130 ml	Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods.	
CUTTER		This leaflet and the specifications of the product have been developed prior to the date of product launch.	
Model	-	Final specifications are subject to change without notice.™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Туре	Rotary cutter	Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list	
MEDIA HANDLING Roll paper	One Roll, Top loading Front Output	to see which variety of paper/media is recon	nmended.
Cassette	Front-loading, Front Output		
Manual feed (1 sheet) Paper path switch (roll/cut sheet)	Top-feeding, Front Output Automatic switch from roll to cassette and vice versa		
Media Types	Plain and coated paper, technical paper, film, photographic paper,		
	proofing paper, backlit, self adhesive, banner and sign, fine art printing material		
l			

imagePROGRAF

Canon Inc. canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V., 2011

FINE Full-photolithography Inkjet Nozzle Engineering Canon (UK) Ltd

Reigate, Surrey RH2 8BF Tel: 01737 220000

Woodhatch

Fax: 01737 220022 www.canon.co.uk



Canon Ireland Arena Road, Sandyford Industrial Estate Dublin 18, Ireland

Tel: 01 2052400 Fax: 01 2958141 www.canon.ie

